



# FOXBOX V4

## All-inclusive video analysis for outdoor detection

**The best remotely monitored outdoor detection solution to turn alarms into immediate and effective alerts.**

FoxBox is easy and fast to install, includes all the hardware and software required to provide an effective and robust site security solution, and offers:

- **Guaranteed effective detection** with an extremely low rate of false alarms,
- **The transformation of alarms into qualified alerts** and immediate video verification for the Alarm Receiving Centers, thanks to instantaneous video push of the alarm.



### ■ ■ ■ NEW FEATURES

- **Performance:** new generation of analysis combined with AI filters for an exhaustive detection without any compromise and a further reduction in false alarms.
- **Range extension:** new models for 12- and 15-channels.
- **Durability:** optimised and more powerful industrial hardware components.
- **Easy to configure:** additional filters available.

The FoxBox is an all-inclusive detection solution designed to be connected to remote monitoring, with 5 models available to suit your needs.

- **Includes:** customised hardware & pre-configured software, plus remote Foxstream support throughout the life of the FoxBox.
- **Range:** 2, 4, 8, 12 and 15 video channels, to suit all types of site.
- **Transmission** of the event to the Alarm Receiving Center in real time (integrated "push" mode), for automatic, instant and qualified video qualification.
- **Plug'n Play:** intuitive interface, simple configuration and maintenance. Integrated video storage (HDD) and I/O terminals.
- **Compatibility:** native integration with remote monitoring reception platforms - ESI, AzurSoft, Immix... and with the SIA DC-09 protocol.
- **Remote access:** point-to-point or multi-site, through a dedicated secure and responsive web interface (mobile, tablet, PC).

## Technical characteristics



VIDEO	2 VIDEO CHANNELS	4 VIDEO CHANNELS	8 VIDEO CHANNELS	12 VIDEO CHANNELS	15 VIDEO CHANNELS
Acquisition type	IP				
Number of video channels	2	4	8	12	15
Acquisition & compression format	RTSP : H264 / H265 / MPEG4 HTTP : MJPEG				
Acquisition frequency	5 to 15 fps (per camera)				
Cameras	Thermal (QVGA, HQVGA, QQVGA resolution) / color				
Analog channel option	Please contact us				
RECORDING					
Storage capacity	1To		2To	4To	
Recording format	Same as acquisition format				
Recording type	Continuous				
Storage period	Up to 30 days				
INTERFACE					
Network interface	2 Ethernet port				
Digital Inputs / output	3 inouts / 3 outputs	5 inputs / 5 outputs	9 inputs / 9 outputs	13 inputs / 13 outputs	15 inputs / 15 outputs
PHYSICAL CHARACTERISTICS					
Dimensions (mm)	L 330 mm x H 55 mm P 240 mm			L 330 mm x H 140 mm P 365 mm	
Power supply	12 V - 3 A (110/220 V power supply)			220 V (wire supplied)	
Consumption	36 W			55 W	
Operating Temperature	0°C to 50°C - 32°F to 122°F				
Certification	CE, Europe RoHs				
GUARANTEE / SERVICE					
Standard	2 years guarantee (3 years if the product is registered online)				
Premium Service	Advance exchange service with warranty extended to 5 years (equivalent equipment sent within 24 hours after diagnosis by Foxstream support by phone)				

March 2024